ADMOTECH
Advanced Mobile Technology

37-10, Techno 1-ro, Yuseong-gu, Daejeon 34015, South Korea
Phone : +82-42-936-1353 Fax :+82-42-936-1350

DROP-IN Circulator
1200 ~ 1400 MHz ADC130BD(200)

Features

- 23dB typical Isolation, 0.30dB typical Insertion Loss at room temperature.
- Custom products available with alternate configurations such as attenuators, high power terminations, reverse circulation etc.
- Designed for Wireless Telecommunications Systems.
- RoHS Compliant

Options

The customers can choose as followers
- Direction : Clockwise(Default) or Counter Clockwise.

Electrical Characteristics

Parameter	Units	Specifications
Frequency	MHz	1200 ~ 1400
Insertion Loss	dB Max.	0.40
Isolation	dB Min.	21
VSWR	Max.	1.25 : 1
Temperature	°C	- 30 ~ +85
FDW./REV. Power	W Max.	150/100
Input/Output Impedance	Ω	50

Mechanical Dimensions



RoHS Compliant

Package Size : BD
Option Type : none
Direction:Clockwise Default

Unit: mm[inch]
Tolerance: ±0.2mm

If you do not find appropriate frequency range, Please contact with sales@admotech.com