ADMOTECH
Advanced Mobile Technology

37-10, Techno 1-ro, Yuseong-gu, Daejeon 34015, South Korea
Tel :+82-42-936-1353 Fax :+82-42-936-1350

DROP-IN Isolator
2200 ~ 2400 MHz ADI230CET(200)

Features

- 21dB typical Isolation, 0.30dB typical Insertion Loss at room temperature.
- Custom products available with alternate configurations such as attenuators, high power terminations, reverse circulation etc.
- Designed for Wireless Telecommunications Systems.
- RoHS Compliant

Options

The customers can choose as followers
- Direction : Clockwise(Default) or Counter Clockwise.
- T : Termination, A3 : -30dB Attenuator for detection, A2 : -20dB Attenuator for detection

Electrical Characteristics

Parameter	Units	Specifications
Frequency	MHz	2200 ~ 2400
Insertion Loss	dB Max.	0.40
Isolation	dB Min.	19
VSWR	Max.	1.29 : 1
Temperature	°C	- 30 ~ +85
FDW./REV. Power	W Max.	150/100
Input/Output Impedance	Ω	50

Mechanical Dimensions



RoHS Compliant

Package Size : CE
Option Type : T
Direction:Clockwise Default

Unit: mm[inch]
Tolerance: ±0.2mm

If you do not find appropriate frequency range, Please contact with sales@admotech.com